




# PRODUCTS SPECIFICATIONS

## Power Supply

<p><b>PSPI-12V15W (Plug-In)</b></p> <ul style="list-style-type: none"> <li>▪ Power Input: 120/240VAC</li> <li>▪ Power Output: 12VDC – 15W</li> <li>▪ Protection: Hiccup with auto recovery to 1.1 to 1.3 I<sub>o</sub></li> <li>▪ Temperature Range: (32°F to 104°F) 0°C to 40°C</li> <li>▪ Application: Indoor. Outdoor: needs to be housed in a weather proof cover</li> <li>▪ Approval: UL, CE</li> </ul>	 <p>A small, black, rectangular plug-in power supply with a two-prong AC cord and a DC output terminal.</p>
<p><b>PSWI-12V20W (Wire-In)</b></p> <ul style="list-style-type: none"> <li>▪ Power Input: 120/240VAC</li> <li>▪ Power Output: 12VDC – 20W</li> <li>▪ Protection: Over-voltage, Over current and Short circuit protection: Auto-recovery</li> <li>▪ Temperature Range: (-22°F to 140°F) -30°C to 60°C</li> <li>▪ Application: Indoor and Outdoor, Suitable for damp location</li> <li>▪ Approval: UL, CE</li> </ul>	 <p>A small, beige, rectangular wire-in power supply with two AC input wires and two DC output wires.</p>
<p><b>PSWI-12V40W (Wire-In)</b></p> <ul style="list-style-type: none"> <li>▪ Power Input: 120/240VAC</li> <li>▪ Power Output: 12VDC – 40W</li> <li>▪ Protection: Over-voltage, Over current and Short circuit protection: Auto-recovery</li> <li>▪ Temperature Range: (-22°F to 140°F) -30°C to 60°C</li> <li>▪ Application: Indoor and Outdoor, Suitable for damp location</li> <li>▪ Approval: UL, CE</li> </ul>	 <p>A larger, beige, rectangular wire-in power supply with two AC input wires and two DC output wires. The label includes technical specifications and safety markings.</p>