




# PRODUCTS SPECIFICATIONS

## Touch Control Units

<p><b>TPSU100</b> (Touch Pad Sensor Unit)</p> <ul style="list-style-type: none"> <li>▪ Power Input: 12VDC – 24W (2A)</li> <li>▪ Power Output: 12VDC – 24W (2A)</li> <li>▪ Temperature Range: (-40°F to 185°F) -40°C to 85°C</li> <li>▪ Application: Indoor, Outdoor: Suitable for damp location if sealed with silicon after all connections completed and housed in a weather proof box, see recommended 3<sup>rd</sup> party products.</li> </ul>	
<p><b>TPSU100T</b> (Touch Pad Sensor Unit with Timer)</p> <ul style="list-style-type: none"> <li>▪ Power Input: 12VDC – 24W (2A)</li> <li>▪ Power Output: 12VDC – 24W (2A)</li> <li>▪ Temperature Range: (-40°F to 185°F) -40°C to 85°C</li> <li>▪ Timer: 10 seconds to 1-1/2 hours settings</li> <li>▪ Application: Indoor, Outdoor: Suitable for damp location if sealed with silicon after all connections completed and housed in a weather proof box, see recommended 3<sup>rd</sup> party products.</li> </ul>	
<p><b>SP-CX1000</b> (Sensor Pad)</p> <ul style="list-style-type: none"> <li>▪ Size: 2.3" x 3.8"</li> <li>▪ Temperature Range: (-40°F to 115°F) -40°C to 46°C</li> <li>▪ Application: Indoor and Outdoor. Suitable for wet locations</li> <li>▪ Recommended Use: Wall</li> <li>▪ Compatibility: Use with Tilit™ TPSUs only</li> <li>▪ Feature: Adhesive backer for ease of installation</li> <li>▪ Wire Length Requirement: Maximum 7 feet and Minimum 3 feet</li> </ul>	
<p><b>SP-CX2000</b> (Grid Sensor Pad)</p> <ul style="list-style-type: none"> <li>▪ Size: 7.5" x 11.5"</li> <li>▪ Temperature Range: (-40°F to 115°F) -40°C to 46°C</li> <li>▪ Application: Indoor and Outdoor. Suitable for wet locations</li> <li>▪ Recommended Use: Floor, where greater sense area is required</li> <li>▪ Compatibility: Use with Tilit™ TPSUs only</li> <li>▪ Feature: Adhesive backer for ease of installation</li> <li>▪ Wire Length Requirement: Maximum 7 feet and Minimum 3 feet</li> </ul>	